

# THE ULTIMATE OVERHEAD GARAGE DOOR OPENER

## SUPER QUIET OPERATION AND A HOST OF FEATURES

With a powerful 1000N DC motor, adjustable speed settings and ready for Wireless Safety Beams, the Enduro™ is the opener of choice for when you positively want the best in performance, features and peace of mind.

Ready for the most demanding of applications, the Enduro™ has all the features you need. The powerful 1000N DC motor has variable speed settings to best match your door, including a slow speed option for tilt doors. The aluminium C-Rail provides corrosion resistance, and can be paired with belt drive for near silent operation. In addition, the Service Indicator lets you know when it is time to service your door. Other standard features include the secure TrioCode™128 transmitter system, LED courtesy lighting, Wireless Safety Beam compatibility, Door Profiling and Intelligent Safety Systems. Optional modes comprise Auto Close for extra security protection, Ventilation Mode for cooling and Vacation Modes for prolonged absences.

## WHAT'S IN THE BOX:



Opener with LED Courtesy Lights



Wall mounted TrioCode™128 control panel



Two TrioCode™128 transmitters

### AT A GLANCE:



## SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes\*) for the ultimate in security.

\*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

#### **BELT DRIVEN QUIETNESS**

The ultimate companion to a quiet DC motor, the optional belt drive ensures your opener operates without the clatter that chain driven units have. The belt is impregnated with steel cables to ensure long life and strength.

#### **POWERFUL DC MOTOR**

The three speed 1000N DC motor is custom designed to work with the most demanding of residential custom and tilt door applications.

#### **5-YEAR WARRANTY**

The Enduro™ is backed by a 5-year/10,000 cycle warranty, giving peace-of-mind that you are choosing the most reliable automation solution.

SMART SIMPLE SECURE

# ROGDO-9 GEN2

# **TECHNICAL SPECIFICATIONS**

Power	Input Voltage	230-240V a.c. 1-phase
	Transformer Rating	150VA
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Peak Driving Force	1000N
Door Sizes	Rated Door Area	18m²
	Typical Travel Speed (door dependent)	90mm/sec (Setting 1) 110mm/sec (Setting 2) 130mm/sec (Setting 3)
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 <sup>38</sup> code combinations (340,282,366,920,938,463,463,374,607,431,768,211,456 codes)
	Transmitter Type	TrioCode™128
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	2 x LED
	Safety Beam Compatibility	2 x Wireless/2-wire Safety Beams
Warranty		5 year/10,000 cycles

#### **SAFETY & SECURITY FEATURES**



Soft Start/Soft Stop



**Intelligent Safety System** 



**Door Profiling** 



TrioCode™128



#### **POWER & MOUNTING SYSTEMS**



DC Motor - 1000N



Belt Drive (optional)



Low Headroom

#### **OPERATING MODES & FEATURES**



Wireless Safety Beams Ready



**LED Courtesy Lights** 



Auto Close (with Safety Beams)



Service Indicator



Ventilation Mode



**Vacation Mode** 



**Auxiliary Output** 

See our website for our icon glossary explanations.

**Proudly Distributed by:** 

#### ENHANCE YOUR OPENER TO MATCH YOUR LIFESTYLE



Battery Back Up In the event of power failure your door will still work



Wireless Safety Beams Extra peace of mind that protects children and pets, plus enables Auto-Close functions.



Wireless Keypad Weatherproof, secure access without a transmitter or keys is great for school kids and active families.



www.facebook.com/ATA.Openers

a u t  $^{f Q}$  m a t i c